


STRETCH WRAPPING TECHNOLOGY

Stretch film wrapper GL Robot

Stretch wrapping – the efficient method to secure stacked pallet loads.



Benefits	The GL Robot is a mobile stretch wrapper. The handle, with powered control buttons, allows easy transportation of the wrapper to the package. Replacing of the film roll is easy and fast with the (optional) flip-open stretch unit. Wrapping operation by simple touch controls. This modular machine is suitable for both light and heavy use.	
Technical data		
Machine	Supply	battery 110 AH, 24 V (2 x 12 V)
	Charger	230 V, ca. 1 kW
	Capacity	150 pallets per battery charge, depending on wrapping program.
	Weight	325 kg
	Speed	max. 90 mtr./ min
	Pre-stretch	option 1) mechanical brake, 2) electrical brake, 3) motorized 150 - 200 - 250%
Machine function	- infinitely variable speed turntable - infinitely variable speed film carriage - number of adjustable upper and lower windings - pallet height sensing - up and down winding - rainproof program - manual: - turntable speed, - film carriage up and down	
Pallet load	Length/ Width,	min. 600 x 600, max. unlimited
	Pallet height	2,1 mtr
	Pallet weight	unlimited
Stretch film	Material	LLDPE (Cyklop stretch)
	Width/ Diameter	500 mm/ max. 250 mm
	Thickness	17 - 30 mμ
	Core diameter	76 mm
	Weight	max. 18 kg
Options	- mast extension 2,4 mtr. and 2,8 mtr. - photo cell for black film. - double guide wheel - pre-stretch unit with mechanical brake - pre-stretch unit with electric brake - pre-stretch unit with motorized pre-stretch	

[illegible]